



Video
Analytics



8MP



POE



Bandwidth
76Mbps

Specification	
OSD Language	Multiple Languages
Mechanical design	Dimension (WxDxH) 300*227*53mm
Electrical	Input Voltage/Current: DC48V, PoE Swith: 48V /1.5A Power consumption (excluding hard disk): 6W
Operating Temperature/Humidity	Temperature: 0°C~+40°C (32°F ~ 104°F) Humidity: Less than 90%RH
Video Resolution	8MP, 5MP, 3MP, 2MP(1080P), 1.3MP(960P), 1.0MP(720P)
Recording Bandwidth	Inputs: 76Mbps Out: 32Mbps
Installation wizard	Yes
Compression	Audio: G.711A, G.711U Video: H.264 / H.264+ / H.265 / H.265+
Frame rate	4K: 30fps 4MP: 60fps 2MP: 120fps
AI	Yes
Event	MD (Sensitivity Level 1~8), Videlo loss, Beep, Email, Push notification to Mobile APP
Playback function	Fast forward / backward (2x, 4x, 8x,16x) Slow forward (1/2x, 1/4x, 1/8x, 1/16x)
Playback	Max 4CH playback
Fisheye	Use WEB CMS, device does not support
Local	UI5.0
WEB	IE10/11
Mobile viewer	Bolide Quick Connect
P/W Reset	Factory Reset: Press 10 seconds
VGA	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080)
HDMI	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080, 2560*1440, 3840*2160/EDID)
POE	8 PoE ports; single port up to 802.3at (30w)
Ethernet	1 RJ45 100/100 Base-T
USB	USB2.0*1 (front) USB2.0*1+ (rear)
Audio out	Yes, 1
E-sata	No
HDD	1 SATA HDD, up to 10TB
Line in	No
RS485	No
Alarm Input/out	No

* Specifications Are Subject to Change Without Notice.